



## SCHEDA TECNICA N° 244

# DECOR WAX

## WATER-BASED TRANSPARENT PROTECTIVE FINISHING.

**FEATURES:** "DECOR WAX" is a siliconic protective product exclusively for internal surfaces. Due to its particular formula, it is used to protect the previous application of "DÉCOR" products (when it is mentioned in the technical data sheet). It is ideal to enhance the decorative effect and gives "DÉCOR" product a velvet appearance.

Further, it provides them with a strong resistance against washings, spots and wear and tear. It is easy to apply and has a very low environmental impact and it results to be odourless, therefore it is possible to apply it in small rooms. Its application does not alterate the normal permeability of the treated support.

**SUPPORT PREPARATION:** The surface must be perfectly dry, free from chalking and greased parts, from moulds and bacteria.

**APPLICATION:** every type of brush. Use protective equipment during the manipulation of the product. Mix manually before use with a stainless steel or wood trote (do not use electronic mixers). Apply the product with light circular movements. Apply when the temperatures are between +10°C and + 30°C. Do not apply on hot or frost surfaces, in case of strong wind or when there is a high humidity percentage. Before to start the application, cover and protect other surfaces such as doors, windows, furnishings and floors. Apply DECOR WAX only when the decorative product on the wall is perfectly dry. Apply the second layer after 4-8 hours from the first application if necessary.

**ASPETTO:** Transparent liquid.

**DILUTION:** 1 ÷ 1 in volume with water. Only mix manually during the dilution and/or before use

**VISCOSITY:** 14" $\pm$  2 Ford 4 at 23  $\pm$  2°C.

**SPECIFIC WEIGHT:** Kg./lt.: 1,01  $\pm$  0,03 at 23  $\pm$  2°C.

Seconda Edizione. Data di compilazione: 02.12.2008. La presente annulla e sostituisce la precedente.

1

Quanto riportato è frutto delle nostre migliori conoscenze ed esperienze. L'utilizzatore finale è comunque tenuto a mettere in atto prove preventive per appurare l'idoneità del prodotto all'uso richiesto ed è responsabile della sua messa in opera.

---



---



**THEORIC COVERAGE:**

Sqm./lt.: 20 - 25 per each layer.

**DRYING PROCESS:**

1 hr. To the touch, paintable after 4-8 hrs. 12 hrs in depth (a  $23 \pm 2$  °C)

**LAVAGGIO ATTREZZI:**

With water immediately after use

**CONFEZIONI DI VENDITA:**

12 x 1 lts. buckets.

**COLOUR:**

Transparent. "DECOR WAX" only enhance the colour of the decorative product, according to the type of support and its nature

**STORAGE**

---

Keep in a cool dry place, far from frost and from the reach of children